

															1 A	±	
Esc	P1	F2	F3	F4	FS	F6	87	FB	F9	F10	F11	F12 Rolen2	Pause	Pos 1	Ende	Einfg	Druck
*	:	2 :	\$ 3 •	\$ 4	% 5	& 6	7 ((8 [) 91	= 0 }	? 8 \	;	+	Num B	÷	*	-
₩.	Q	w	e.	R	т	z	U	1	0	Р	0	*	÷.	7 Pos 1	8 †	9 Bid†	
Ð	A	s	D	F	G	н	J	к	L	ō	Ä	•	-	4 ←	5	6 →	
Û	> < 1	Y	x	с	v	в	N	M µ	;	:	Ξ	1) Dean	Entf	1 Ende	2 ↓	3 Bild+	+ Erter
Strg	En	Win	At					AtGr		Strg	Bidt	t	Bid+	0 Einfg		, Ent	

Models may vary from the image shown

The AK-C7000 is a high quality, high performance, and highly reliable PC-keyboard. The purification and disinfection capacity makes it a perfect fit in hospitals, at practitioners and in microbiological laboratories. The silicone membrane protects keyboard and key field against ingress of dirt and fluids.

The AK-C7000 impresses with congenial key actuation and precise key guidance. With its full PC key layout, the AK-C7000 is highly recommendable for heavy duty type writing in hygiene critical applications. The AK-C7000 increases protection against infection and limits risk and liability of the health care provider.

FUNCTION AND PERFORMANCE

- ightarrow Hygiene Keyboard for Clinical Wipe Disinfection
- → Clinical Wipe Disinfection with all common Disinfectants according to German Guidelines VAH/DGHM
- → Utmost Writing Comfort by Scissors Balancing Technology
- → Perfect Type Writing in Hygiene Critical Applications
- → Clean Function allows to switch off Keys during Cleaning Process

TECHNICAL DATA

Weight main product:	730 g
Weight of product without packaging:	796 g
Dimensions product without packaging:	374 mm x 139 mm x 25 mm

Weight of product incl. packaging:						
Dimensions product incl. packaging:	395 mm x 195 mm x 30 mm					
Content of master carton (pieces):	20					
Weight of master carton incl. content:	17,500 g					
Dimensions master carton:	410 mm x 340 mm x 420 mm					
Cable-length:	180 cm					
Storage temperature:	-20 °C - 60 °C					
Working temperature:	0 °C - 50 °C					
Product approvals:	 CE EU RoHS FCC EN60601-1-2-2015 (IEC 4th edition) 					
System Requirements- Hardware:	USB-A					
Operating system:	All operating systems that support USB keyboard interface					
Scope of delivery:	KeyboardManual					
Switching characteristics:	tactile					
Max. current consumption (mA) of keyboard:	25 mA					
Actuating force (cN):	60 cN					
Total Key Travel:	3 mm					
Key labeling:	Silk screen printing on silicon membrane					
Number of keys:	104					
Special key functions:	FN KeyCleanFunction					
Status LEDs:	in housing					
Key technology:	Scissor					
Keycap material:	ABS					
Warranty:	2 years warranty					

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

 1 / 2 © Cherry Digital Health GmbH • Rosental 7, c/o Mindspace, D-80331 Munich Phone +49 9643 2061100 • www.cherry.de
 Postal Address: Cherrystr. 2, 91275 Auerbach i.d.OPf., Germany



EAN & Part number	Protection class	Color	Layout
7061117572401 AK-C7000F-UVS-B/GE	IP 68	black	DE (Germany)
7061111596502 AK-C7000F-UVS-B/NOR	IP 68	black	PN (PanNordic)
7061114105749 AK-C7000F-UVS-B/UK	IP 68	black	GB (United Kingdom)
7061111047837 AK-C7000F-UVS-W/FR	IP 68	white	FR (France)
7061112750354 AK-C7000F-UVS-W/GE	IP 68	white	DE (Germany)
7061111015959 AK-C7000F-UVS-W/NOR	IP 68	white	PN (PanNordic)
7061117230943 AK-C7000F-UVS-W/UK	IP 68	white	GB (United Kingdom)
7061116486259 AK-C7000F-UVS-W/US	IP 68	white	US (USA)
7061113781838 AK-C7000F-U1-B/GE	Standard	black	DE (Germany)
7061113477038 AK-C7000F-U1-B/NOR	Standard	black	PN (PanNordic)
7061117257438 AK-C7000F-U1-B/UK	Standard	black	GB (United Kingdom)
7061118207135 AK-C7000F-U1-W/FR	Standard		FR (France)
7061115035083 AK-C7000F-U1-W/GE	Standard		DE (Germany)
7061111106930 AK-C7000F-U1-W/NOR	Standard		PN (PanNordic)
7061111772272 AK-C7000F-U1-W/UK	Standard		GB (United Kingdom)
7061117205385 AK-C7000F-U1-W/US	Standard		US (USA)